



FIRST FLOOR SLAB RC DETAILS

NOTES:

1. ALL DIMENSIONS ARE LEVELS ARE FOOT AND INCHES UNLESS STATED OTHERWISE.
2. GRADE OF CONCRETE SHALL BE M20
3. CLEAR COVER TO OUTERMOST REINFORCEMENT SHALL BE 3/4" FOR SLAB.
4. READ THIS DRG ALONGWITH RELAVANT ARCH. DRG. DISCREPANCY IF ANY SHOULD BE BROUGHT TO THE NOTICE OF THE ENGINEER.
5. Y - DENOTES HIGH YIELD STRENGTH DEFORMED BARS HAVING YIELD STRENGTH NOT LESS THAN 415 N/mm<sup>2</sup> CONFORMING TO IS. 1786-1985.
6. LAP LENGTH SHALL BE 40 TIMES DIA.OF BAR AND SHALL BE KEPT STAGGERED.

- NOTES:
1. PROVIDE DISTRIBUTOR FOR SLAB S1,S2,S3,S4. Y8 @9" C/C.
  2. SLAB THICKNESS 5"

1.	RO	02-05-06	RELEASED FOR CONSTRUCTION	
SLNO	REV.	DATE	DESCRIPTION	SIGN

PROJECT:-  
PROPOSED SCHOOL BUILDING  
AT SOLINGANALLUR.

CLIENT:-  
M.CHANDRASEKAR.

TITLE:- FIRST FLOOR SLAB RC DETAILS		SHEET 1 OF 1	
DRAWN	DESKRAL	CHECKED	AS
DESIGNED	AS	APPROVED	RSR
DWG.NO:- YD/PRO/CS/RC/16		DATE : 18-04-2006	SCALE 1:8
			REV. RO